

32  
(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
28 December 2000 (28.12.2000)

PCT

(10) International Publication Number  
WO 00/79670 A1

(51) International Patent Classification<sup>7</sup>: H02K 1/14, 15/02

(21) International Application Number: PCT/EP00/05037

(22) International Filing Date: 2 June 2000 (02.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PD99A000130 18 June 1999 (18.06.1999) IT

(71) Applicant (for all designated States except US): ASKOLL  
HOLDING S.R.L. [IT/IT]; Via Industria, 30, I-36031  
Dueville (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MARIONI, Elio  
[IT/IT]; Via Molino, 6, I-36031 Dueville (IT).

(74) Agent: MODIANO, Guido; Modiano, Via Meravigli, 16,  
I-20123 Milano (IT).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ,  
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,  
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,  
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,  
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,  
UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,  
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: STATOR FOR SYNCHRONOUS MOTORS HAVING MORE THAN TWO POLES



(57) Abstract: A stator for synchronous motors with more than two poles, comprising a plurality of sectors (10) formed by lamination packs which are joined at their ends (11), forming as a whole a closed annular structure, at least one pole shoe (13) protruding from each one of the sectors (10). The ends of the stator define, at each connecting region (14), thanks to respective facing shaped portions (15), at least one tab (16) with mutually opposite undercuts (17), one for each end; the tabs (16) accommodate corresponding portions of an elastic connecting element (18) which surrounds the tab and rigidly couples the sectors.

WO 00/79670 A1

## STATOR FOR SYNCHRONOUS MOTORS HAVING MORE THAN TWO POLES

### Technical Field

The present invention relates to a stator for synchronous motors having  
5 more than two poles.

### Background Art

It is known that single-phase permanent-magnet synchronous motors are currently provided by means of a stator configuration S which is shaped like a tuning fork (see Figure 1 of the accompanying drawings), which has been  
10 very successful thanks to its low cost arising from its extreme constructive simplicity.

The windings, not shown in Figure 1, are formed on spools with winding machines which have a high production rate, can be easily automated and therefore have an unbeatable investment/productivity ratio.

15 The coils are then very easily fitted on the respective pole shoes of the stator.

Moreover, Figure 1 clearly shows that the process for blanking the metal laminations that compose the stator pack minimizes waste, thanks to the tuning-fork geometry, which allows two contours to interpenetrate.

20 In synchronous motors having a stator with more than two poles, the structure is necessarily more complicated.

Figure 2, for example, illustrates the diagram of a four-pole stator in which there is a ring A on the inside whereof there are four dovetail slots B for the interlocking insertion of complementarily shaped ends C of pole  
25 shoes D.

In this case also, the windings, not shown, are produced on spools by means of winding machines and the coils are fitted on the pole shoes D.

Finally, the pole shoes D are inserted in the ring A with an interlocking coupling.

30 In this case, construction of the stator is complicated, because the ring A

becomes very expensive as it entails a large amount of waste in the blanking process, while the interlocking coupling of the pole shoes D with the ring A causes problems related both to coupling tolerances (if they are too small, assembly is particularly difficult, whereas if they are too large, one introduces a loss in the magnetic circuit and an insufficient structural solidity of the stator, with the risk of introducing unwanted vibrations) and to assembly, which must occur at right angles to the plane of the stator, with consequent complications in the assembly process.

In order to solve these problems, motors have been devised in which the stator (see Figure 3) is constituted by a plurality of sectors E which are joined at their ends, forming as a whole a closed annular structure.

A pole shoe F protrudes from each sector E and is monolithic therewith.

The ends G are complementarily shaped, forming male-female interlocking couplings H, and constitute, as a whole, seats I for mutual fixing screws, not shown.

In this case, the monolithic annular element is eliminated, but there is still the need to interlock the last sector E by acting on a plane which is perpendicular to the stator plane, with the consequent coupling problems, although greater structural solidity is achieved by means of the screws.

The interlocking couplings H moreover introduce asymmetry problems which make it necessary to orientate the pack during assembly.

The amount of waste is reduced with respect to the preceding case.

#### **Disclosure of the Invention**

The aim of the present invention is to provide a stator for synchronous motors having more than two poles which allows to fit coils wound beforehand on spools by means of winding machines in a simple manner on each one of the poles before assembly.

Within the scope of this aim, a consequent primary object is to provide a stator which avoids the need to orientate the components during mutual assembly.

Another object is to eliminate any kind of interlocking between the parts, so as to eliminate the problems related to the mechanical coupling tolerance in order to facilitate assembly.

Another important object is to minimize the amount of waste during the  
5 blanking process.

These and other objects which will become better apparent hereinafter are achieved by a stator for synchronous motors with more than two poles, comprising a plurality of sectors formed by lamination packs which are joined at their ends, forming as a whole a closed annular structure, at least  
10 one pole shoe protruding from each one of said sectors, characterized in that said ends define, at each connecting region, by respective facing shaped portions, at least one tab with opposite undercuts, one for each end, said tabs accommodating corresponding portions of an elastic connecting element which surrounds said tab and rigidly couples the sectors.

#### 15 **Brief Description of the Drawings**

Further characteristics and advantages of the invention will become apparent from the detailed description of embodiments thereof, illustrated only by way of non-limitative example in the accompanying drawings, wherein:

- 20 Figure 1 is a plan view of two laminations of a first conventional stator;
- Figure 2 is a perspective view of a second conventional stator pack;
- Figure 3 is a perspective view of a third conventional stator pack;
- Figure 4 is a plan view of a first embodiment of the pack of a stator according to the invention;
- 25 Figure 5 is a perspective view of the stator pack of Figure 4;
- Figure 6 is a plan view of a stator in a second embodiment of the invention;
- Figure 7 is a plan view of a third embodiment of the pack of a stator according to the invention;
- 30 Figure 8 is a perspective view of the stator pack of Figure 7;

Figure 9 is a view of the blanking lines of a portion of metal plate from which the components of the pack of Figure 7 are obtained.

### **Ways of carrying out the Invention**

With reference to the above cited Figures 4 and 5, a stator for  
5 synchronous motors having more than two poles comprises, in a first embodiment, four sectors 10 formed by lamination packs which are joined at their ends 11, forming as a whole a closed annular structure 12, which in this case has a substantially octagonal shape.

In particular, each sector 10 forms, with its middle portion, one wall of  
10 the annular structure and forms, with its ends, respective wall portions which are inclined at 45 sexagesimal degrees with respect to the rest.

At least one pole shoe 13 protrudes toward the center of the annular structure 12 in the middle region of each sector 10.

According to the invention, the ends 11, at each mutual coupling region  
15 14, rest against each other edge to edge by means of flat surfaces and define, together with respective facing shaped portions 15, at least one tab 16, which has a circular profile in the case being considered.

The tab 16 can be internal and/or external (as shown by the dashed lines of Figure 4).

20 As a whole, each sector 10 is symmetrical with respect to a longitudinal middle plane.

The region where the portions 15 of the tab 16 connect to the corresponding ends 11 is, as a whole, narrower than the diameter of the tab 16, so that mutually opposite undercuts 17 (one for each end 11) are formed  
25 which accommodate corresponding end portions of an elastic coupling element which is constituted, in this case, by a spring 18 made of metal plate which completely surrounds said tab 16 and rigidly couples the sectors.

The force with which the spring 18 acts depends of course on the material that composes it and on its geometry.

30 In practice, the undercuts 17 form inclined planes and/or dovetail

elements on which longitudinal edges 19 of the spring 18 act; the spring is shaped appropriately, in this case, like a longitudinally open cylinder.

With reference now to the above cited Figure 6, a stator for a six-pole motor is illustrated which is constituted by six sectors 110, each of which  
5 forms a wall of an annular structure 112 which has a hexagonal contour.

Each sector 110 has a pole shoe 113 in its middle region; in this case, the spool 120 of the corresponding winding of the pole shoe, not shown for the sake of simplicity, is shown inserted.

In this case also, the ends 111 are joined by means of facing flat surfaces  
10 114 by virtue of contoured portions 115 which form tabs 116 having a circular profile and on which coupling springs 118 act.

With reference now to the above cited Figures 7 to 9, in another embodiment the stator of a four-pole motor is composed of four sectors 210, whose ends 211 lie at right angles to the middle regions provided with the  
15 pole shoes 213.

The sectors 210 are therefore E-shaped and form, as a whole, a closed cross-shaped annular structure 212.

Mutual coupling occurs in the same manner as in the preceding cases, with contoured portions 215 which form tabs 216 which have a circular  
20 profile and on which springs 218 shaped like a longitudinally open cylinder are fitted.

Figure 9 illustrates the blankings produced on a portion of metal plate 221 from which the components 210a (laminations) of each sector 210 are obtained.

25 The E-shaped figures perfectly interpenetrate, providing considerable savings in raw material and optimizing the process.

In practice it has been observed that in all the embodiments the stator according to the invention has achieved the intended aim and objects.

The provision of a composite outer annular structure of the stator in fact  
30 allows to provide the windings separately from said stator and then fit them

on the pole shoes before assembly.

The perfect symmetry of each sector with respect to the others avoids the need to orientate the parts for mutual assembly.

The springs which, thanks to their elasticity, adapt to the shapes and  
5 dimensions of the tabs, eliminate the problems in terms of coupling  
tolerances between the parts.

Moreover, optimization of the shapes of each sector ensures a reduction of the blanking waste of the laminations that compose the stator, providing considerable savings in raw material and optimizing the process.

10 The invention thus conceived is susceptible of numerous modifications and variations, all of which are within the scope of the appended claims.

All the details may furthermore be replaced with other technically equivalent elements.

In practice, the materials used, so long as they are compatible with the  
15 contingent use, as well as the dimensions, may be any according to  
requirements.

The disclosures in Italian Patent Application No. PD99A000130 from which this application claims priority are incorporated herein by reference.

### CLAIMS

1. A stator for synchronous motors with more than two poles, comprising a plurality of sectors formed by lamination packs which are joined at their ends, forming as a whole a closed annular structure, at least one pole shoe protruding from each one of said sectors, characterized in that said ends  
5 define, at each connecting region, thanks to respective facing shaped portions, at least one tab with mutually opposite undercuts, one for each end, said tabs accommodating corresponding portions of an elastic connecting element which surrounds said tab and rigidly couples two  
10 adjacent sectors.
2. The stator according to claim 1, characterized in that each one of said sectors is symmetrical with respect to a longitudinal middle plane.
3. The stator according to one or more of the preceding claims, characterized in that said sectors are identical.
- 15 4. The stator according to claim 1, characterized in that said ends rest against each other with flat surfaces.
5. The stator according to claim 1, characterized in that said tab has a circular profile.
6. The stator according to claim 1, characterized in that said tab is  
20 internal and/or external with respect to said annular structure.
7. The stator according to claim 1, characterized in that said connecting region where said portions that compose said tab connect to the corresponding ends of the sectors is, as a whole, narrower than the diameter of said tab.
- 25 8. The stator according to claim 1, characterized in that said elastic element is constituted by a spring made of metal plate which completely surrounds said tab.
9. The stator according to claim 8, characterized in that said spring is shaped like a longitudinally open cylinder.
- 30 10. The stator according to claim 1, characterized in that in a four-pole



case each one of said sectors forms, with a middle portion thereof, a wall of the annular structure, and forms, with ends thereof, respective wall portions which are inclined with respect to the rest by 45 sexagesimal degrees.

11. The stator according to claim 1, characterized in that in a four-pole  
5 case the ends of each sector lie at right angles to middle regions provided with pole shoes, each sector being E-shaped, said sectors forming, as a whole, a closed cross-shaped annular structure.

12. The stator according to claim 1, characterized in that in a six-pole  
case each one of said sectors forms a wall of an annular structure which has  
10 a hexagonal contour.




FIG. 1 PRIOR ART




FIG. 2  
PRIOR ART







FIG. 3  
PRIOR ART



3/3






Fig. 8



## INTERNATIONAL SEARCH REPORT

Internat'l Application No

PCT/EP 00/05037

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H02K1/14 H02K15/02

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H02K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	PATENT ABSTRACTS OF JAPAN vol. 008, no. 063 (E-233), 24 March 1984 (1984-03-24) -& JP 58 212337 A (MATSUSHITA DENKI SANGYO KK), 10 December 1983 (1983-12-10) abstract	1-10, 12
Y	PATENT ABSTRACTS OF JAPAN vol. 010, no. 313 (E-448), 24 October 1986 (1986-10-24) & JP 61 124241 A (MATSUSHITA ELECTRIC IND CO LTD), 12 June 1986 (1986-06-12) abstract	1-10
Y	DE 875 227 C (SIEMENS SCHUCKERTWERKE AG) 30 April 1953 (1953-04-30) figure 9	12
	--- -/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&amp;\* document member of the same patent family

Date of the actual completion of the international search

12 September 2000

Date of mailing of the international search report

18/09/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 851 epo nl,  
Fax: (+31-70) 340-3018

Authorized officer

Roy, C

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/05037

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 644 767 A (KASARGOD SADANAND VITHAL ET AL) 22 February 1972 (1972-02-22) figure 1 -----	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/05037

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 58212337 A	10-12-1983	NONE	
JP 61124241 A	12-06-1986	NONE	
DE 875227 C		NONE	
US 3644767 A	22-02-1972	FR 2086616 A	31-12-1971